



## Solutions

- 17" touch monitor
- High performance, high efficiency and stability
- Prompt processing and convenient scalability
- Excellent multi-touch technology & Bright, clean screen
- "Free-Moving" by stand and Organizing cable wires
- Manufacture by our own technology, "Made in Korea"
- Provide the best Customer Service rapidly

## Application



## Specification

Category		Specification
LCD Panel	Screen Diagonal Pixel HxY Aspect Ratio Support Color White Luminance Contrast Ratio	17" Active Matrix TFT LCD 1280X1024 4:3 Ratio 16.7M color 350[cd/m2] 1000:1[Typ.]
Touch Panel	Type Interface OS supported	4/5-wire resistive touch screen USB/RS232 DOS, WIN, LINUX, IMAX
Video Input	Input Signal Sync Range Viedo Cable	Analog RGB / USB 56Hz~75Hz(V)/30kHz~60kHz(H) D-Sub 15 pin Cable, DVI-D Cable
OSD Control	OSD Button	Power/Select/Menu/Up/Down
Power	Type Input Voltage Output Voltage Consumption	Combo Internal AC & External DC Adapter Universal AC 100~230V, 50/60 Hz DC12V/5V(Inverter/mail), 2.5A 20W
Environment	Temperatures Humidity	Operating : 0~40, Storage : -20~60 Operating : 30~85%, Storage : 5~90%