



Solutions

- 15" touch monitor
- High performance, high efficiency and stability
- Prompt processing and convenient scalability
- Excellent multi-touch technology & Bright, clean screen
- LCD monitor with SCR and MSR device
- "Free-Moving" by stand and Organizing cable wires
- Manufacture by our own technology, "Made in Korea"
- Provide the best Customer Service rapidly

Application



Specification

| Category | | Specification |
|-------------|--|--|
| LCD Panel | Screen Diagonal Pixel HxY Aspect Ratio Support Color White Luminance Contrast Ratio | 15" Active Matrix TFT LCD 1024 X 768 4:3 Ratio 16.2M/262K color 250[cd/m2] 500:1[Typ.] |
| Touch Panel | Type Interface OS supported | 4/5-wire resistive touch screen USB/RS232 DOS, WIN, LINUX, IMAX |
| Video Input | Input Signal Sync Range Viedo Cable | Analog RGB / USB 56Hz~75Hz(V)/30kHz~60kHz(H) D-Sub 15 pin Cable, DVI-D Cable |
| OSD Control | OSD Button | Power/Select/Menu/Up/Down |
| Power | Type Input Voltage Output Voltage Consumption | Combo Internal AC & External DC Adapter Universal AC 100~230V, 50/60 Hz DC12V/5V(Inverter/mail), 2.5A 20W |
| Environment | Temperatures Humidity | Operating : 0~40, Storage : -20~60 Operating : 30~85%, Storage : 5~90% |